


[→ PRINT THIS PAGE](#)
[x CLOSE WINDOW](#)

## Specifications

<b>Model Name</b>	VFR800F 08
<b>Engine Type</b>	Liquid-cooled 4-stroke 16-valve DOHC 90° V-4
<b>Bore &amp; Stroke</b>	72 x 48mm
<b>Displacement</b>	781.7cm <sup>3</sup>
<b>Compression Ratio</b>	11.6:1
<b>Carburettor(s)</b>	PGM-FI electronic fuel injection
<b>Maximum Power</b>	80kW/10,500rpm
<b>Maximum Torque</b>	80Nm/8,750rpm
<b>Ignition</b>	Computer-controlled digital transistorised with electronic advance
<b>Starter</b>	Electric
<b>Transmission</b>	6-speed
<b>Final Drive</b>	'O'-ring sealed chain
<b>Dimensions (mm)</b>	2,120 x 735 x 1,195 (LxWxH)
<b>Wheel Base (mm)</b>	1,460
<b>Seat Height (mm)</b>	805
<b>Ground Clearance (mm)</b>	130
<b>Fuel Capacity (litres)</b>	22
<b>Front Wheel</b>	17M/C x MT3.50 'U'-section 6-spoke cast aluminium
<b>Rear Wheel</b>	17M/C x MT5.50 'U'-section 5-spoke cast aluminium
<b>Front Tyres</b>	120/70 ZR17M/C (58W)
<b>Rear Tyres</b>	180/55 ZR17M/C (73W)
<b>Front Suspension</b>	43mm H.M.A.S. cartridge-type telescopic fork with stepless preload adjustment, 109mm axle travel
<b>Rear Suspension</b>	Pro-Link with gas-charged H.M.A.S. damper, 7-step preload and stepless rebound damping adjustment, 120mm axle travel
<b>Front Brakes</b>	296 x 4.5mm dual floating hydraulic disc with combined 3-piston calipers and sintered metal pads
<b>Rear Brakes</b>	256 x 6mm hydraulic disc with combined 3-piston caliper and sintered metal pads
<b>Dry Weight (kg)</b>	213
<b>Warranty Period</b>	24 Months

<b>Price</b>	\$15,990.00 + ORC (includes GST)* RRP
<b>blah</b>	blah2

---

