

Bonneville Specification:

ENGINE:		
Type		Air-cooled, DOHC, parallel-twin, 360° firing interval
Capacity		865cc
Bore/Stroke		90 x 68mm
Compression Ratio		9.2:1
Fuel System		Twin carburettors with throttle position sensor and electric carburettor heaters.
Exhaust		Stainless steel headers, twin chrome silencers
Ignition		Digital-inductive type
TRANSMISSION:		
Primary Drive		Gear
Final Drive		X ring chain
Clutch		Wet, multi-plate
Gearbox		5-speed
Throttle body diameter		∅36.8
Gear Ratios		Primary: 108/62 1 st : 41/15 2 nd : 37/19 3 rd : 34/22 4 th : 31/24 5 th : 29/27 Final: 43/18
Oil Capacity		4.5 litres (1.2 US gals)
CYCLE PARTS:		
Frame		Tubular steel cradle
Swingarm		Twin-sided, tubular steel
Wheels	Front	36-spoke 19 x 2.5in
	Rear	40-spoke 17 x 3.5in
Tyres	Front	100/90 19
	Rear	130/80 R 17
Suspension	Front	Kayaba, 120mm travel, 41mm forks
	Rear	Kayaba chromed spring twin shocks with adjustable preload, 106mm rear wheel travel
Brakes	Front	Single 310mm disc, Nissin 2 piston floating caliper
	Rear	Single 255mm disc, Nissin 2 piston floating caliper
Instrument display/functions		Analogue speedometer with odometer and trip information
DIMENSIONS:		
Length		2,230mm (87.8in)
Width (Handlebars)		740mm (29.1in)
Height		1,100mm (43.3in)
Seat Height		775mm (30.5in)
Wheelbase		1,500mm (59.1in)
Rake/Trail		28°/110mm
Weight (Dry)		205kg (451lbs)
Fuel Tank Capacity		16.0 litres (4.2 gal US)
PERFORMANCE:		

Triumph Motorcycles Limited

Normandy Way, Hinckley, Leicestershire, LE10 3BZ United Kingdom

Telephone +44 (0)1455 251700, Facsimile +44 (0)1455 453005

www.triumphmotorcycles.com



(MEASURED AT CRANKSHAFT TO DIN 70020)		
Maximum Power		67PS (66bhp/49kW) at 7,200rpm
Maximum Torque		71Nm (52ft.lbf) at 6,000rpm